Newtop Chemical Materials (Shanghai) Co.,Ltd.

Technical Indicators

U-CAT SA 506 catalyst CAS122987-42-7 Sanyo Japan

U-CAT SA 506 is a thermal latent alkali generator. It is a p-toluenesulfonate of 1,

8-diazabicyclic [5.4.0]undec-7-ene (DBU). DBU is a strong base commonly used in

organic chemistry. However, it is not very stable at room temperature and will break

down, releasing ammonia. U-CAT SA 506 is more stable than DBU and does not release

ammonia until it is heated to about 160 degrees Celsius. This makes it a safer and more

convenient alternative to DBU for use in organic synthesis.

Product Details

U-CAT SA 506 is a white, odorless powder. It dissolves in water and most organic

solvents. It is stable at room temperature and can be stored for a long time.

Physical and chemical properties

CAS Number: 122987-42-7

Molecular Formula: C14H21N5O3S

Molecular weight: 307.39 g/mole

Density: 1.30 g/cm³

Melting point: 170-172 degrees Celsius

Boiling point: 270-272 degrees Celsius

Solubility: Soluble in water, ethanol, chloroform

Newtop Chemical Materials (Shanghai) Co.,Ltd.

Technical Indicators

NEWTOP

Use

U-CAT SA 506 is used as a catalyst in a variety of organic syntheses. It is particularly

suitable for reactions that require a strong base, such as the Diels-Alder reaction and

the Suzuki-Miyaura reaction.

Pros

More stable than a DBU

No ammonia release

Easy to use

Precautions

• U-CAT SA 506 is a strong base that can cause skin and eye irritation.

It is important to wear gloves and goggles when handling U-CAT SA 506.

• U-CAT SA 506 is flammable and should be stored in a cool, dry place.

Newtop Chemical Materials (Shanghai) Co.,Ltd. **Technical Indicators**

Shelf life:

Remain unopened for two years

Storage and Transportation:

Should be sealed, stored in a dry cool ventilated warehouse

Packing:

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper

ventilation. After the original packaging, please fasten the packaging cover as soon as

possible to prevent moisture and other substances from mixing and affecting the

product performance. Do not inhale dust and avoid contact between skin and mucous

membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and

change after work. Store contaminated clothes separately and use them after washing.

Practice good hygiene.

Newtop Chemical Materials (Shanghai) Co.,Ltd. Technical Indicators



	Technical support	t and business	contacts E-mail:	info@newto	pchem.com
--	-------------------	----------------	------------------	------------	-----------